Stainless Steel Inline Flow Meters

1.5" Meter V3040-15 or V3040BSPT-15	2" Meter V3094-15 or V3094BSPT-15	Arrow of the second sec
• 1.5" Inline meter suited for commercial/industrial applications	• 2" Inline meter suited for commercial/industrial applications	 3" Inline meter suited for commercial/industrial applications
 316 stainless steel	 316 stainless steel	 316 stainless steel
material	material	material
 Electro polished for	 Electro polished for	 Electro polished for
improving corrosion	improving corrosion	improving corrosion
resistance, leaving a	resistance, leaving a	resistance, leaving a
lasting bright finish	lasting bright finish	lasting bright finish
 Service flow range 0.5	 Service flow range 1.5	 Service flow range 3.5
to 75 gpm (2-284 lpm)	to 150 gpm (5.7-568 lpm)	to 350 gpm (13-1,325 lpm)
• Meter accuracy ±5%	• Meter accuracy ±5%	• Meter accuracy ±5%
 Reliable and proven	 Reliable and proven	 Reliable and proven
turbine design	turbine design	turbine design
• 15-foot cable included	• 15-foot cable included	• 15-foot cable included
• 1.5" Male x Female NPT	• 2" Male x Female NPT	• 3" Male x Female NPT
or BSPT connections	or BSPT connection	or BSPT connection



Certified to NSF/ANSI/CAN 61 and NSF/ANSI 372.